





Logistics





# Model

Print Method Direct Thermal Resolution 203 dpi (8 dots/mm) Printing Width 72mm Paper separator 48mm/52mm/56mm/64mm/68mm/76mm (option) Memory Input buffer: 256k bytes NV Flash: 2M Interface USB+Bluetooth/USB+Wifi Print Speed 80mm/s

## **Fonts**

Fonts	Alphanumeric; Simplified Chinese, Traditional
	Chinese; 35 International Character Sets

## Barcode

1D	UPC-A, UPC-E, EAN-8, EAN-13, CODE 39, ITF,
	CODE 128, CODE 93
2D	QR code, PDF417
J-83 93 9982	

## Detection

Paper out, cover open, black mark detection Sensors

### **Power Supply**

7.4V rechargeable Li-ion battery, 1800mAh
AC 100V-240V 50/60HZ
DC 5V, 1A
4 hours
105 hours
2.3 hours

#### Paper

Paper Type	Thermal Receipt Paper
Paper Width	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Paper Thickness	0.053~0.15mm
Roll Dia	Мах. <b>Ф50</b> mm (O.D)
Paper Load	Easy paper loading
Paper Cut	Manual tear

-2°C ~ 52°C, 10% ~ 85% R.H, no-condensing -20 ~ 60°C, 5 ~ 90% R.H, no-condensing

## **Physical Charateristics**

Working Condition

Storage Condition

Dimensions	117(D)x110(W)x57(H)mm
Net weight	Net weight: 0.48kg Gross weight: 0.5kg
Accessories	
Accessories	USB data cable, power adapter, manual, partition board, battery
Reliability	
Printing head	50KM
Packing	

Individual box	Dimension 140×137×113mm 1unit/carton
Master carton	Dimension 300×295×368mm 12unit/carton

#### OS

Emulation	ESC/POS
Driver	Windows XP /Vista/ Win7/Win8 /Win10/
	Win 2000/Win CE/OPOS/JPOS
SDK	Android, IOS